

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line : W22 NEMA Premium Efficiency Three-Phase			Product code : 11993104			
Frame	:	447/9T	Locked rotor time	:	23s (cold) 13s (hot)	
Output	:	200 HP (150 kW)	Temperature rise	:	80 K	
Poles	:	8	Duty cycle	:	Cont.(S1)	
Frequency	:	60 Hz	Ambient temperature	:	-20°C to +40°C	
Rated voltage	:	575 V	Altitude	:	1000 m.a.s.l.	
Rated current	:	203 A	Protection degree	:	IP55	
L. R. Amperes	:	1300 A	Cooling method	:	IC411 - TEFC	
LRC	:	6.4x(Code H)	Mounting	:	F-1	
No load current	:	92.0 A	Rotation ¹	:	Both (CW and CCW)	
Rated speed	:	890 rpm	Noise level ²	:	66.0 dB(A)	
Slip	:	1.11 %	Starting method	:	Direct On Line	
Rated torque	:	163 kgfm	Approx. weight ³	:	1401 kg	
Locked rotor torque	:	200 %				
Breakdown torque	:	220 %				
Insulation class	:	F				
Service factor	:	1.15				
Moment of inertia (J)	:	6.78 kgm ²				
Design	:	B				
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	94.5	95.0	95.0	Max. traction	:	2438 kgf
Power Factor	0.62	0.73	0.78	Max. compression	:	3839 kgf
Losses at normative operating points (speed;torque), in percentage of rated output power						
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
5.4	4.3	3.8	2.9	2.0	1.5	1.0
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	NU-322 C3		6319 C3		
Sealing	:	WSeal		WSeal		
Lubrication interval	:	13000 h		17000 h		
Lubricant amount	:	60 g		45 g		
Lubricant type	:	Mobil Polyrex EM				
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	13/01/2024				1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 11993104



Performance : 575 V 60 Hz 8P

Rated current	: 203 A	Moment of inertia (J)	: 6.78 kgm ²
LRC	: 6.4	Duty cycle	: Cont.(S1)
Rated torque	: 163 kgfm	Insulation class	: F
Locked rotor torque	: 200 %	Service factor	: 1.15
Breakdown torque	: 220 %	Temperature rise	: 80 K
Rated speed	: 890 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	13/01/2024			