

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :							
Product line	: W22 NEMA Premium Efficiency Three-Phase	Product code :	12004236				
Frame	: 444/5TC	Cooling method	: IC411 - TEFC				
Insulation class	: F	Mounting	: F-1				
Duty cycle	: Cont.(S1)	Rotation <sup>1</sup>	: Both (CW and CCW)				
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line				
Altitude	: 1000 m.a.s.l.	Approx. weight <sup>2</sup>	: 0.0 kg				
Protection degree	: IP55	Moment of inertia (J)	: 2.81 kgm <sup>2</sup>				
Design	: B						
Output [HP]	150	125	125	125	150	150	150
Poles	4	4	4	4	4	4	4
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	340/170	169	160	156	205	194	189
L. R. Amperes [A]	2244/1122	1183	1104	1170	1189	1125	1191
LRC [A]	6.6x(Code G)	7.0x(Code G)	6.9x(Code G)	7.5x(Code H)	5.8x(Code F)	5.8x(Code F)	6.3x(Code G)
No load current [A]	116/58.0	58.0	61.2	64.0	58.0	61.2	64.0
Rated speed [RPM]	1784	1484	1486	1487	1475	1480	1482
Slip [%]	0.89	1.07	0.93	0.87	1.67	1.33	1.20
Rated torque [kgfm]	61.0	61.1	61.0	61.0	73.8	73.6	73.5
Locked rotor torque [%]	200	190	220	229	160	180	190
Breakdown torque [%]	250	240	260	290	200	220	240
Service factor	1.15	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	48s (cold) 27s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)
Noise level <sup>2</sup>	73.0 dB(A)	69.0 dB(A)	69.0 dB(A)	69.0 dB(A)	69.0 dB(A)	69.0 dB(A)	69.0 dB(A)
Efficiency (%)	25%						
	50%	95.4	95.1	95.1	94.8	95.4	95.4
	75%	95.8	95.5	95.5	95.5	95.4	95.4
	100%	95.8	95.3	95.3	95.5	95.0	95.4
Power Factor	25%						
	50%	0.74	0.73	0.70	0.68	0.79	0.76
	75%	0.82	0.83	0.81	0.79	0.85	0.83
	100%	0.85	0.85	0.85	0.84	0.86	0.86
Losses at normative operating points (speed;torque), in percentage of rated output power							
Losses (%)	P1 (0,9;1,0)	4.5	4.5	4.5	4.5	4.5	4.5
	P2 (0,5;1,0)	3.5	3.5	3.5	3.5	3.5	3.5
	P3 (0,25;1,0)	3.1	3.1	3.1	3.1	3.1	3.1
	P4 (0,9;0,5)	2.4	2.4	2.4	2.4	2.4	2.4
	P5 (0,5;0,5)	1.5	1.5	1.5	1.5	1.5	1.5
	P6 (0,5;0,25)	1.1	1.1	1.1	1.1	1.1	1.1
	P7 (0,25;0,25)	0.6	0.6	0.6	0.6	0.6	0.6
Bearing type	: Drive end : NU-319 C3	Non drive end : 6316 C3	Foundation loads				
Sealing	: Viton	Viton	Max. traction	: 1542 kgf			
	: Oil Seal	Oil Seal	Max. compression	: 1542 kgf			
Lubrication interval	: 5000 h	10000 h					
Lubricant amount	: 45 g	34 g					
Lubricant type	: Mobil Polyrex EM						
Rev.	Changes Summary			Performed	Checked	Date	
Performed by							
Checked by					Page	Revision	
Date	18/03/2024				1 / 9		

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Notes  
USABLE @208V 376A SF 1.00 SFA 376A

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	18/03/2024		2 / 9	

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12004236



Performance : 230/460 V 60 Hz 4P

Rated current : 340/170 A  
 LRC : 6.6  
 Rated torque : 61.0 kgfm  
 Locked rotor torque : 200 %  
 Breakdown torque : 250 %  
 Rated speed : 1784 rpm

Moment of inertia (J) : 2.81 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.15  
 Temperature rise : 80 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12004236



Performance : 380 V 50 Hz 4P IE3

Rated current	: 169 A	Moment of inertia (J)	: 2.81 kgm <sup>2</sup>
LRC	: 7.0	Duty cycle	: Cont.(S1)
Rated torque	: 61.1 kgfm	Insulation class	: F
Locked rotor torque	: 190 %	Service factor	: 1.00
Breakdown torque	: 240 %	Temperature rise	: 80 K
Rated speed	: 1484 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 9	Revision
Checked by				
Date	18/03/2024			

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12004236



Performance : 400 V 50 Hz 4P IE3

Rated current : 160 A  
 LRC : 6.9  
 Rated torque : 61.0 kgfm  
 Locked rotor torque : 220 %  
 Breakdown torque : 260 %  
 Rated speed : 1486 rpm

Moment of inertia (J) : 2.81 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 80 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		5 / 9		
Date		18/03/2024		

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12004236



Performance : 415 V 50 Hz 4P IE3

Rated current : 156 A	Moment of inertia (J) : 2.81 kgm <sup>2</sup>
LRC : 7.5	Duty cycle : Cont.(S1)
Rated torque : 61.0 kgfm	Insulation class : F
Locked rotor torque : 229 %	Service factor : 1.00
Breakdown torque : 290 %	Temperature rise : 80 K
Rated speed : 1487 rpm	Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 6 / 9	Revision
Checked by				
Date	18/03/2024			

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12004236



Performance : 380 V 50 Hz 4P IE2

Rated current : 205 A  
 LRC : 5.8  
 Rated torque : 73.8 kgfm  
 Locked rotor torque : 160 %  
 Breakdown torque : 200 %  
 Rated speed : 1475 rpm

Moment of inertia (J) : 2.81 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 105 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		7 / 9		
Date		18/03/2024		

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12004236



Performance : 400 V 50 Hz 4P IE2

Rated current : 194 A  
 LRC : 5.8  
 Rated torque : 73.6 kgfm  
 Locked rotor torque : 180 %  
 Breakdown torque : 220 %  
 Rated speed : 1480 rpm

Moment of inertia (J) : 2.81 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 105 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				



# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12004236



Performance : 415 V 50 Hz 4P IE3

Rated current : 189 A  
 LRC : 6.3  
 Rated torque : 73.5 kgfm  
 Locked rotor torque : 190 %  
 Breakdown torque : 240 %  
 Rated speed : 1482 rpm

Moment of inertia (J) : 2.81 kgm<sup>2</sup>  
 Duty cycle : Cont.(S1)  
 Insulation class : F  
 Service factor : 1.00  
 Temperature rise : 105 K  
 Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				